# Burlington 600 Phase

## astro

#### General

Location:BathroomClass:cULus (Class I)Location Rating:DampDriver Required:Mains 120V

Installation Orientation:Wall Mount - Horizontal & VerticalFitting Method:½" Stub Mount or 4" Octagon Box

with included Canopy Kit

Main Material: Metal - Zinc

 Dimensions (mm):
 H: 600 W: 110 D: 118

 Dimensions (inch):
 H: 23.62 W: 4.33 D: 4.65

Cut Out Hole (mm/inch):

Recess Depth (mm/inch):

Fire Rating:

Cable Length (mm/inch):

Gross Weight (lb):

6.16

Ada Compliant: Yes - if installed in compliance

with ADA 307.2

Ic Rating:

### Lamp

**Light Source:** Mid-Power LED

Wattage: 14.4W
Lamp Included: Yes (Integral)

Maximum Lamp Length (mm/inch):-Luminous Flux (lm):778Colour Temp (K):2700Cri (Ra):90Macadam Ellipse:3-StepTilt Adjustable Angle (°):-Rotation Adjustable Angle (°):-Average Lifetime (hrs):52000

#### Electrical

Beam Angle (°):

Switched: No Dimmable: Yes

**Dimming Method:** Phase - Leading & Trailing Edge

Supply Frequency (Hz):50/60Driver/Ballast Voltage (V):120Driver Average Lifetime (hrs):50000Efficacy (Im/W):54

### Additional Information:

Shade Included: Shade/Diffuser Material: Plastic
Shade/Diffuser Finish: -

F Mark: Suitable for mounting

on flammable materials







Code: 1477015 Finish: Matt Gold



Code: 1477016 Finish: Polished Chrome

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

## **Product Elevations**



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







