
Perch Light Branch

UMUT YAMAC



What is more poetic and elegantly captivating than a bird perched on a branch, flirting, singing and celebrating life? We all recognize this image and steal a moment from our precious time to admire this triumph of nature and beauty. Perch Light Branch by Umut Yamac is a suspension lamp with birds of polycarbonate and synthetic paper perched on a steel and aluminium frame.

Detailing



These sunlit birds are free to swing when softly touched. They gently glow and bring along the promise of spring.


Colours



Brass and white

Perch Light Branch / Large

Dimensions



Product

WIDTH 112cm | 44.1"
HEIGHT 53cm | 20.9"
DEPTH 41cm | 16.1"
WEIGHT NETTO 9kg | 19.84lbs

Packaging

WIDTH 26.5cm | 10.4"
HEIGHT 57.5cm | 22.6"
CUBAGE 0.17m^3 | 6.11ft^3
LENGTH 113.5cm | 44.7"
WEIGHT 9kg | 19.84lbs

Technical CE

ADDITIONAL
Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

MATERIAL
Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL
B

LIGHTSOURCE INCLUDED
Yes

SHAPE
Linear

FREQUENCY
50/60

LAMPHOLDER
LED (Solid state)

CABLE COLOUR
Black

CANOPY
Matching steel cylinder

CRI
80

LIGHT OUTPUT
560 lm

LIGHTSOURCE TYPE
LED

NUMBER OF LIGHTSOURCES
5

INPUT VOLTAGE
180-240V

MAX POWER CONSUMPTION
25W

LIFETIME
50000 hours

CABLE LENGTH
400cm | 157.5"

COLOUR TEMPERATURE
3000 K (max)

LIGHT DIRECTION
All directions

DIMMING & LIGHTING CONTROL

0-10V, 1-10V, Push / Pulse dim on Low Voltage (SELV), Potentiometer

See last page for more information about the dimming possibilities.

CE

Technical UL

ADDITIONAL

Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL

B

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

CANOPY

Matching steel cylinder

CRI

80

LIGHT OUTPUT

560 lm

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

5

INPUT VOLTAGE

90-305V

MAX POWER CONSUMPTION

25W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

3000 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL


1-10V, PWM, Potentiometer

See last page for more information about the dimming possibilities.

c UL us LISTED

Perch Light Branch / Small

Dimensions



Product

WIDTH 73cm | 28.7"
HEIGHT 53cm | 20.9"
DEPTH 36cm | 14.2"
WEIGHT NETTO 7kg | 15.43lbs

Packaging

WIDTH 27.8cm | 10.9"
HEIGHT 58cm | 22.8"
CUBAGE 0.12m^3 | 4.41ft^3
LENGTH 77.5cm | 30.5"
WEIGHT 7kg | 15.43lbs

Technical CE

ADDITIONAL
Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

MATERIAL
Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL
C

LIGHTSOURCE INCLUDED
Yes

SHAPE
Linear

FREQUENCY
50/60

LAMPHOLDER
LED (Solid state)

CABLE COLOUR
Black

CANOPY
Matching steel cylinder

CRI
80

LIGHT OUTPUT
336 lm

LIGHTSOURCE TYPE
LED

NUMBER OF LIGHTSOURCES
3

INPUT VOLTAGE
180-240V

MAX POWER CONSUMPTION
25W

LIFETIME
50000 hours

CABLE LENGTH
400cm | 157.5"

COLOUR TEMPERATURE
3000 K (max)

LIGHT DIRECTION
All directions

DIMMING & LIGHTING CONTROL

0-10V, 1-10V, Push / Pulse dim on Low Voltage (SELV), Potentiometer

See last page for more information about the dimming possibilities.

CE

Technical UL

ADDITIONAL

Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL

C

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

CANOPY

Matching steel cylinder

CRI

80

LIGHT OUTPUT

336 lm

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

3

INPUT VOLTAGE

90-264V

MAX POWER CONSUMPTION

25W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

3000 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

1-10V, PWM, Potentiometer

See last page for more information about the dimming possibilities.

c UL us LISTED

Dimming & Lighting Control

0-10V

The luminaire is dimmable by using an either internally mounted or externally placed 0-10V dimmer switch. 0-10V is a dimming system widely used in some parts of the world, for example in North-America. This method will need its own wiring. Dimming quality is perfect, without flicker, the range can be limited and the luminaire can be dimmed to off. Please note that this is only possible using a 0-10V compatible driver. Contact us for more information.

Compatible models: Large CE, Small CE

1-10V

The luminaire is dimmable by using an either internally mounted or externally placed 1-10V dimmer switch. 1-10V is a dimming system widely used in some parts of the world, for example in North-America. This method will need its own wiring. Dimming quality is perfect, without flicker, the range can be limited and the luminaire cannot be dimmed to off. To turn off the luminaire a switch is needed.

Compatible models: Large CE, Large UL, Small CE, Small UL

Push / Pulse dim on Low Voltage (SELV)

The luminaire is dimmable by using an either internally mounted or externally placed low voltage momentary switch or pushbutton switch. This switch will need its own low voltage wiring. The switch should be of the type 'normal off - momentary on'. The luminaire dims perfectly when the switch makes and holds contact. A short press switches between on and off.

Compatible models: Large CE, Small CE

Potentiometer

The luminaire is dimmable by turning a potentiometer knob that is either internally mounted or externally placed. This dimmer will need its own low voltage wiring, hiring a professional installer is advised. The lamp is perfectly dimmable. Most knobs can be used to also turn the luminaire on/off.

Compatible models: Large CE, Large UL, Small CE, Small UL

PWM

The luminaire is dimmable by using a low voltage Pulse Width Modulation dimmer. This dimmer will need its own low voltage wiring, hiring a professional installer is advised. By using PWM the luminaire will dim perfectly over its

full range. In some cases, a little flicker can be experienced in the lower range.

Compatible models: Large UL, Small UL
