



## PRODUCT SPECIFICATION

### GENERAL

|                                  |  |                          |   |
|----------------------------------|--|--------------------------|---|
| <b>FINISH:</b>                   | Polished Chrome  | <b>GROSS WEIGHT:</b>     | 1.6 (kg)  |
| <b>MAIN MATERIAL:</b>            | Metal - Aluminium                                      | <b>CLASS:</b>            | cETLus (Class I)                                      |
| <b>DIMENSIONS:</b>               | H: 33mm W: 600mm D: 80mm<br>H: 1.29" W: 23.6" D: 3.15" | <b>LISTING LOCATION:</b> | Damp  |
| <b>INSTALLATION ORIENTATION:</b> | Wall Mount - Vertical / Horizontal                     | <b>FITTING METHOD:</b>   | 1/2 StubMount 4" Octagon Box with included Canopy kit |
| <b>CUT OUT HOLE:</b>             | Not Applicable   | <b>ADA COMPLIANT:</b>    | Yes   |
| <b>RECESS DEPTH:</b>             | Not Applicable   | <b>IC RATING:</b>        | Not Applicable  |
| <b>FIRE RATING:</b>              | Not Applicable   | <b>VOLTAGE:</b>          | Mains 120 (V)   |
| <b>CABLE LENGTH:</b>             | Not Applicable   |                          |   |


### LAMP

|                             |                |                                   |                |
|-----------------------------|----------------|-----------------------------------|----------------|
| <b>LIGHT SOURCE:</b>        | Mid Power LED  | <b>MACADAM ELIPSE:</b>            | 3-Step         |
| <b>MAXIMUM WATTAGE:</b>     | 7.2W           | <b>UGR:</b>                       | Not Applicable |
| <b>MAXIMUM LAMP LENGTH:</b> | Not Applicable | <b>BEAM ANGLE:</b>                | Not Applicable |
| <b>LAMP INCLUDED?</b>       | Yes (Integral) | <b>TILT ADJUSTMENT ANGLE:</b>     | Not Applicable |
| <b>DELIVERED LUMENS:</b>    | To Be advised  | <b>ROTATION ADJUSTMENT ANGLE:</b> | Not Applicable |
| <b>COLOR TEMP:</b>          | 3000 (K)       | <b>AVERAGE LIFESPAN:</b>          | 60,000 (Hrs)   |
| <b>CRI:</b>                 | 80             | <b>L70:</b>                       | To Be Advised  |
| <b>R9:</b>                  | To Be Advised  |                                   |                |

### ELECTRICAL

|                               |                |                                  |                |
|-------------------------------|----------------|----------------------------------|----------------|
| <b>SWITCHED:</b>              | No             | <b>SUPPLY FREQUENCY:</b>         | 50/60 (Hz)     |
| <b>DIMMABLE:</b>              | No             | <b>DRIVER / BALLAST VOLTAGE:</b> | 120 (V)        |
| <b>DIMMING METHOD:</b>        | Not Applicable | <b>DRIVER AVERAGE LIFESPAN:</b>  | 50,000 (Hrs)   |
| <b>DRIVER OUTPUT CURRENT:</b> | 350 (mA)       | <b>EFFICACY:</b>                 | To Be Advised  |
| <b>DRIVER OUTPUT VOLTAGE:</b> | Not Applicable | <b>DRIVER INCLUDED?</b>          | Yes (Integral) |

## ADDITIONAL INFORMATION



BOX QUANTITY X6

# PRODUCT ELEVATIONS

---

