

Ako 600 Phase

astro

General

Location:	Interior
Class:	cULus (Class I)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	Wall Mount - Vertical
Fitting Method:	½" Stub Mount, 3x2" Switch Box, 4" Octagon Box with included Canopy Kit and 4x2" Handy Box
Main Material:	Metal - Aluminium
Dimensions (mm):	H: 600 W: 130 D: 88
Dimensions (inch):	H: 23.62 W: 5.12 D: 3.46
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	5.04
Ada Compliant:	Yes
Ic Rating:	-

Lamp

Light Source:	COB LED
Wattage:	15.8W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (lm):	480
Colour Temp (K):	2700
Cri (Ra):	90
Macadam Ellipse:	3-Step
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	55400
Beam Angle (°):	-

Electrical


Switched:	No
Dimmable:	Yes
Dimming Method:	Phase - Leading & Trailing Edge
Supply Frequency (Hz):	50/60
Driver/Ballast Voltage (V):	120
Driver Average Lifetime (hrs):	50000
Efficacy (lm/W):	31

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	-



CODE: 1481023
FINISH: MATT BLACK/GOLD



CODE: 1481024
FINISH: MATT WHITE/GOLD

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

