GINESTRA 300

astro

GENERAL

LOCATION: CLASS: LOCATION RATING: DRIVER REQUIRED: INSTALLATION ORIENTATION: FITTING METHOD: MAIN MATERIAL: DIMENSIONS (mm): DIMENSIONS (inch): CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (lb): ADA COMPLIANT:

cULus (Class 1) Dry Mains 120V Ceiling Mount 4" Octagon Box Metal - Mild Steel H: 2058 Ø: 300 H: 81.02 Ø: 11.81 --1800 / 70.87 5.32 Yes - if installed in compliance with ADA 307.4

Interior

IC RATING:

LAMP

LIGHT SOURCE:	E
WATTAGE:	4
RECOMMENDED LAMP:	1
LAMP INCLUDED:	١
MAXIMUM LAMP LENGTH (mm/inch):	1
LUMINOUS FLUX (Im):	L
COLOUR TEMP (K):	L
CRI (Ra):	L
MACADAM ELLIPSE:	L
TILT ADJUSTABLE ANGLE (°):	-
ROTATION ADJUSTABLE ANGLE (°):	-
LIFETIME (hrs):	L
BEAM ANGLE (°):	L

ELECTRICAL

SWITCHED:	No
DIMMABLE:	Yes
DIMMING METHOD:	Lamp Dependent
SUPPLY FREQUENCY (Hz):	-
DRIVER/BALLAST VOLTAGE (V):	-
DRIVER LIFETIME (hrs):	-
EFFICACY (Im/W):	Lamp Dependent

ADDITIONAL INFORMATION:

SHADE INCLUDED:	-
SHADE/DIFFUSER MATERIAL:	-
SHADE/DIFFUSER FINISH	-
F MARK:	-

E26/Medium 43W 12W Max LED E26/Medium No 145 Lamp Dependent Lamp Dependent Lamp Dependent Lamp Dependent

Lamp Dependent Lamp Dependent



CODE: 1361005 FINISH: MATT BLACK



CODE: 1361007 FINISH: LIGHT GREY



CODE: 1361008 FINISH: MATT WHITE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

