Fuse 3

astro

General

Location:	Interior
Class:	cULus (Class 1)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	Wall Mount - Horizontal or Vertical
Fitting Method:	Included Junction Box
Main Material:	Metal - Mild Steel
Dimensions (mm):	H: 200 W: 75 D: 102
Dimensions (inch):	H: 7.87 W: 2.95 D: 4.02
Cut Out Hole (mm/inch):	L: 194 W: 67.1 / L: 7.64 W: 2.64
Recess Depth (mm/inch):	70 / 2.76
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	2.64
Ada Compliant:	Yes
Ic Rating:	IC Rated

Lamp

Light Source:	High Power LED
Wattage:	3.3W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (lm):	141
Colour Temp (K):	2700
Cri (Ra):	90
Macadam Ellipse:	3-Step
Tilt Adjustable Angle (°):	90
Rotation Adjustable Angle (°):	330
Average Lifetime (hrs):	51000
Beam Angle (°):	18

Electrical

Switched:	Yes
Dimmable:	No
Dimming Method:	-
Supply Frequency (Hz):	50-60
Driver/Ballast Voltage (V):	100-277
Driver Average Lifetime (hrs):	100000
Efficacy (lm/W):	43

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	Suitable for mounting on flammable materials

CODE: 1215091
FINISH: MATT WHITE

CODE: 1215092
FINISH: MATT BLACK

CODE: 1215093
FINISH: POLISHED CHROME

CODE: 1215094
FINISH: MATT NICKEL

CODE: 1215095
FINISH: BRONZE

CODE: 1215102
FINISH: MATT GOLD

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

75mm / 2.95"

4mm / 0.14"

astro

102mm / 4.01"

32mm / 1.26"

70mm / 2.75"

66mm / 2.6"

200mm / 7.87"

193mm / 7.6"

UL CERTIFIED