

# FLOS

F6602046 Bronze


## Taccia

Designed by Achille and Pier Giacomo Castiglioni, 1962

28W - N/Dlm - 2700K



Table lamp providing indirect and reflected light. Reflector in painted aluminium, gloss white on the outside and matt white on the inside. Directionable diffuser in transparent mouth-blown glass. Body in matt black. silver anodized or bronze anodized aluminium. Base in nickel-plated metal. Electric cable of useful length 220 cm, with dimmer switch for ON/OFF and adjustment of the light flow between 10-100%. Plug-in power supply with interchangeable plugs.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8059607006696
Mounting	Table floor
Environment	Indoor dry location
Light source type	LED
LED type	LED array
Lamp holder	COB LED
Power (W)	28
System flux (lm)	N/D

### Physical


Colour	Bronze
Cord length (mm)	2200
Net weight (kg)	10.74
Package volume (m3)	0.18
IP	20

### Download


Mounting instructions	<a href="#">↓ PDF</a>
Mounting instructions	<a href="#">↓ PDF</a>
Spare Parts	<a href="#">↓ PDF</a>

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user



<https://professional.flos.com/en/global/product/taccia-f6602046/>

F6602046

©2022 Flos - P.IVA 00290820174 - 9/22/2022

professional.flos.com | info@flos.com 1/3

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

## Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700

## Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/48
Driver	Remote included
Dimming type	Electronic 48V
Cord length (mm)	2200
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

## Spare Parts



F6510000

Taccia transparent diffuser & reflector



F6608046

Anodized bronze base



RF00780

White reflector



RF6608100

Jack plug with cable and push dimmer



RF3320400

Black plug assembly kit & 48V driver