



09.8405.GX Lacquered Green

### Gustave Residential NEW

Designed by Vincent Van Duysen, 2022



Gustave is a portable, self-powered luminaire, specially designed for tabletop lighting applications and other related uses as supplementary lighting. Gustave's compact size encloses a perfect mix of the most innovative optical and light technology and a disruptive engineering, developed in the service of a discretionary purpose of Flos for this project: to create the first portable luminaire on the market with circular design awareness, ecological and honestly conceived against obsolescence. Portable luminaire with autonomous battery, designed for residential applications. Powered by 'Button Type 18650 Li-Ion' batteries (2 units, included inside the product). USB-C charging cable (plug adapter not included). 0-100% sequential regulation by means of capacitive haptic push button.

Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 

# ø155 ø120

## Main specifications

Mounting	Table
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	2.5
System power (W)	2.5
Source flux (lm)	221
System flux (lm)	159
Efficacy (Im/W)	69

#### **Physical**

Colour	Lacquered Green	
Length (mm)	155	
Cord colour	Black	
Cord length (mm)	1200	
Net weight (kg)	0.78	
Package height (cm)	36	
Package width (cm)	21	
Package length (cm)	21	
Package volume (m3)	0.02	
IP internal	54	

Download  Mounting instructions	<b>⊥</b> PDF
Photometric Files LDT/IES	<b>⊥</b> ZIP
Technical Drawings	<u>↓</u> ZIP
3D	.↓. ZIP

https://professional.flos.com/en/global/product/gustave-residential-09.8405.gx/

09.8405.GX










#### Schematic light drawing



Beam Angle:		145
h(m)	E(lx)	D(m
1	22	6.28
2	6	12.56
3	2	18.84
4	1	25.11
		24.20

Beam	Angle:	145°
h(m)	E(lx)	D(m
1	22	6.28
2	6	12.56
3	2	18.84
4	1	25.11

# Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	100
Beam angle C0-180 (°)	144
Beam angle C90-270 (°)	144

#### Electrical

Insulation class	III	
LED voltage Vf (Vdc)	5	
LED current (mA)	180	
Dimmable	Yes	
Dimming type	Dimmable	
Dimming interface	Dimmer Integrated	
Plug type	Type A	
Batteries inside	Yes	
Battery type	LI-IO	
Charging cycles guaranteed	500	
Charging max power	1 A	
Charging min time	5.5	
Charging socket/connector	USB-C	

#### **Notes**

Product Battery autonomy: 100% - 6 hours / 50% - 10 hours / 25% - 18 hours. Batteries included. USB-A / USB-C Cable included. Adapter 5V, min 2A not included. **Ecodesign and Energy** 

This product contains a light source of energy efficiency

> Replaceable (LED only) light source by a professional

Replaceable control

gear by an end-user

Labelling

class G

#### **Accessories & Power Supply**



#### **OPTIONAL**

RF25965

Adapter 5V. Min 2A | EUR USA UK



#### **OPTIONAL**

RF27576

Adapter 5V. Min 2A. EUR / USA /



Pack 2x Battery for Gustave	08.0744.00
Residential	
Cable for Gustave Residential	08.0761.14
USB-A/USB-C	
Cable for Gustave Residential	08.0761.30
USB-A/USB-C	



#### Electrical

08 07/// 0/

Pack 2x Battery for Gustave Residential



#### Cable

08 0761 14

Cable for Gustave Residential USB-A/USB-C



#### Cable

08.0761.30

Cable for Gustave Residential USB-A/USB-C