

POSE PORTABLE LED



POSE is a series of high output lamps based on conical forms that playfully explores the world of optical physics, through the world of flat lenses often seen in lighthouses, traffic lights and in scientific instruments. With anthropomorphic charm, POSE manipulates light into focused, magnified beams with striking effect. A strong silhouette and touch of humour define its personality, while precise adjustability and high light output ensures adaptability and functionality for any space, domestic or contract. Balancing functionality with minimal design, POSE radiates light and individuality with equal brilliance.

Year of Design	2024
Product Weight	2.30 lb
Finishing Process	Coloured Plastic
Power Method	Rechargeable
Number of Ports	1
Battery Operating Time	Approx 6-9 hours
Battery Charging Time	5 hours
Cable Spec	AWM 2464 22AWG VW-1 1A 80 °C 300V
Cable Type/Length	USB-A to Magnetic, 78.7in
Light Source	3W LED
Max Wattage	3W
Lumens	220
CRI	>90
Colour Temperature	2700K, 3000K
Dimmability	Touch Dimmable
Voltage	5V
Environment	Indoor, IP20
Spares	LEDPB03; POBAT01; POMC01
Certification/Electrical Class	Certified for NZ/AUS



PUTTY

Code	POPO01PUUN
Shade Material	Polycarbonate
Shade Colour/Finish	Putty, Gloss
Base Material	Polycarbonate
Base Colour/Finish	Putty, Gloss
Service Offer	NEW

KELP

Code	POPO01KEUN
Shade Material	Polycarbonate
Shade Colour/Finish	Kelp, Gloss
Base Material	Polycarbonate
Base Colour/Finish	Kelp, Gloss
Service Offer	NEW

INDIGO

Code	POPO01INUN
Shade Material	Polycarbonate
Shade Colour/Finish	Indigo, Gloss
Base Material	Polycarbonate
Base Colour/Finish	Indigo, Gloss
Service Offer	NEW

POSE PORTABLE LED



POSE is a series of high output lamps based on conical forms that playfully explores the world of optical physics, through the world of flat lenses often seen in lighthouses, traffic lights and in scientific instruments. With anthropomorphic charm, POSE manipulates light into focused, magnified beams with striking effect. A strong silhouette and touch of humour define its personality, while precise adjustability and high light output ensures adaptability and functionality for any space, domestic or contract. Balancing functionality with minimal design, POSE radiates light and individuality with equal brilliance.

Year of Design	2024
Product Weight	2.30 lb
Finishing Process	Silver(Plated), Gold(PVD)
Power Method	Rechargeable
Number of Ports	1
Battery Operating Time	Approx 6-9 hours
Battery Charging Time	5 hours
Cable Spec	AWM 2464 22AWG VW-1 1A 80 °C 300V
Cable Type/Length	USB-A to Magnetic, 78.7in
Light Source	3W LED
Max Wattage	3W
Lumens	220
CRI	>90
Colour Temperature	2700K, 3000K
Dimmability	Touch Dimmable
Voltage	5V
Environment	Indoor, IP20
Spares	LEDPB03; POBAT01; POMC01
Certification/Electrical Class	Certified for NZ/AUS




POSE TASK LIGHT LED



POSE is a series of high output lamps based on conical forms that playfully explores the world of optical physics, through the world of flat lenses often seen in lighthouses, traffic lights and in scientific instruments. With anthropomorphic charm, POSE manipulates light into focused, magnified beams with striking effect. A strong silhouette and touch of humour define its personality, while precise adjustability and high light output ensures adaptability and functionality for any space, domestic or contract. Balancing functionality with minimal design, POSE radiates light and individuality with equal brilliance.

Year of Design	2024
Product Weight	5.40 lb
Finishing Process	Coloured Plastic
Cable Spec	UL E348531 2x0,75mm ² , 300V, 80°C
Cable Type/Length	Black Fabric, 98.4in
Light Source	6W LED
Max Wattage	7.5W
Lumens	800
CRI	>90
Colour Temperature	2700K
Dimmability	Inline Dimmable
Voltage	100-240V
Environment	Indoor, IP20
Spares	LEDRING12A; LEDTC11UN
Certification/Electrical Class	Certified for NZ/AUS



POSE TASK LIGHT LED



POSE is a series of high output lamps based on conical forms that playfully explores the world of optical physics, through the world of flat lenses often seen in lighthouses, traffic lights and in scientific instruments. With anthropomorphic charm, POSE manipulates light into focused, magnified beams with striking effect. A strong silhouette and touch of humour define its personality, while precise adjustability and high light output ensures adaptability and functionality for any space, domestic or contract. Balancing light and individuality with equal brilliance.

Year of Design	2024
Product Weight	5.40 lb
Finishing Process	Silver(Plated), Gold(PVD)
Cable Spec	UL E348531 2x0,75mm ² , 300V, 80°C
Cable Type/Length	Black Fabric, 98.4in
Light Source	6W LED
Max Wattage	7.5W
Lumens	800
CRI	>90
Colour Temperature	2700K
Dimmability	Inline Dimmable
Voltage	100-240V
Environment	Indoor, IP20
Spares	LEDRING12A; LEDTC11UN
Certification/Electrical Class	Certified for NZ/AUS



PUTTY

Code	POTL11PU-TUN01M1
Shade Material	Polycarbonate
Shade Colour/Finish	Putty, Gloss
Fitting Code	LEDTC11UN
Base Material	Polycarbonate
Base Colour/Finish	Putty, Gloss
Service Offer	NEW

KELP

Code	POTL11KE-TUN01M1
Shade Material	Polycarbonate
Shade Colour/Finish	Kelp, Gloss
Fitting Code	LEDTC11UN
Base Material	Polycarbonate
Base Colour/Finish	Kelp, Gloss
Service Offer	NEW

INDIGO

Code	POTL11IN-TUN01M1
Shade Material	Polycarbonate
Shade Colour/Finish	Indigo, Gloss
Fitting Code	LEDTC11UN
Base Material	Polycarbonate
Base Colour/Finish	Indigo, Gloss
Service Offer	New

SILVER

Code	POTL11SS-TUN01M1
Shade Material	ABS Plastic
Shade Colour/Finish	Silver, Gloss
Fitting Code	LEDTC11UN
Base Material	ABS Plastic
Base Colour/Finish	Silver, Gloss
Service Offer	NEW

GOLD

Code	POTL11GO-TUN01M1
Shade Material	ABS Plastic
Shade Colour/Finish	Gold, Gloss
Fitting Code	LEDTC11UN
Base Material	ABS Plastic
Base Colour/Finish	Gold, Gloss
Service Offer	New