TECHNICAL DRAWINGS

MADAME CACHET Ø30CM **D080330S-XX**
DIA 30CM/11.8” - H. 33CM/13”

delivery unit: 1
packaging: 45x45xH49cm - 0,1m^3 - 4,7 kg

MADAME CACHET Ø40CM **D080340S-XX**
DIA 40CM/15.7” - H. 43CM/16.9”

delivery unit: 1
packaging: 45x45xH49cm - 0,8m^3 - 6,3 kg

MADAME CACHET Ø50CM **D080350S-XX**
DIA 60CM/23.6” - H. 61CM/24”

delivery unit: 1
packaging: 64x64xH69cm - 0,3m^3 - 12 kg

TECHNICAL DRAWINGS

STANDING LAMPS WIRED

Light source	Dimmable LED included
Colour temperature	2.200K +/-200
Voltage	Power adapter input 100-240V AC / output 12V DC
Wattage	2,5W
Average lifetime	30.000 hrs
Cycles on/off	> 10.000
Starting time	Within 1 sec
Warm-up time to 60% of the full light output	Immediately full light output
Light source dimensions	178 x 85 mm
Luminous flux	80 Lumen/Watt
Luminous efficacy	80 Lumen/Watt
Lumen maintenance	95% 3600H
Colour rendering index	Ra. 80
Energy class	G
Battery	No
Bluetooth	No
Cable	3,8m Cable fixed to luminary, IP65 connector, 20cm cable, AC/DC Power adapter
Control	On/off button
Dimmable	button 1st press: 33% , 2nd press: 66%,3rd press: 100%, 4th press: OFF
Extra	No
Certificates	CE-EMC / CE-RED EN62778 IEC60598-2-4 RoHS 2.0 UKCA IP65 UL/FCC