# TECHNICAL DRAWINGS

**MADAME CACHET Ø30CM** **D080330S-XX**
**DIA 30CM/11.8” - H. 33CM/13”**

delivery unit: 1
packaging: 45x45xH49cm - 0,1m$^3$ - 4,7 kg

**MADAME CACHET Ø40CM** **D080340S-XX**
**DIA 40CM/15.7” - H. 43CM/16.9”**

delivery unit: 1
packaging: 45x45xH49cm - 0,8m$^3$ - 6,3 kg

**MADAME CACHET Ø50CM** **D080350S-XX**
**DIA 60CM/23.6” - H. 61CM/24”**

delivery unit: 1
packaging: 64x64xH69cm - 0,3m$^3$ - 12 kg

# TECHNICAL DRAWINGS

**STANDING LAMPS WIRED**

| | |
|---|---|
| Light source | Dimmable LED included |
| Colour temperature | 2.200K +/-200 |
| Voltage | Power adapter input 100-240V AC / output 12V DC |
| Wattage | 2,5W |
| Average lifetime | 30.000 hrs |
| Cycles on/off | > 10.000 |
| Starting time | Within 1 sec |
| Warm-up time to 60% of the full light output | Immediately full light output |
| Light source dimensions | 178 x 85 mm |
| Luminous flux | 80 Lumen/Watt |
| Luminous efficacy | 80 Lumen/Watt |
| Lumen maintenance | 95% 3600H |
| Colour rendering index | Ra. 80 |
| Energy class | G |
| Battery | No |
| Bluetooth | No |
| Cable | 3,8m Cable fixed to luminary, IP65 connector, 20cm cable, AC/DC Power adapter |
| Control | On/off button |
| Dimmable | button 1st press: 33% , 2nd press: 66%,3rd press: 100%, 4th press: OFF |
| Extra | No |
| Certificates | CE-EMC / CE-RED<br>EN62778<br>IEC60598-2-4<br>RoHS 2.0<br>UKCA<br>IP65<br>UL/FCC |