

FLOS

F018E21K013 Pale Green

In Vitro Unplugged


Designed by Philippe Starck, 2020

115lm - 2700K - CRI> 90 - Beam° 106



Portable outdoor lamp emitting direct light through Edge Lighting technology. Aluminium structure with carrying handle. Optical switch sensor on the head enables 4-step dimming: 100% – 50% – 3% – OFF. Provides up to 6 hours of use. Rechargeable via USB-C.

In Vitro Unplugged was designed by Philippe Starck as a smaller, portable version of the In Vitro series, maintaining the same refined aesthetic while offering greater flexibility. Inspired by the idea of a contemporary lantern, it features an elegant, minimal frame that creates the illusion of an empty glass volume illuminated from within. The design captures Philippe Starck's signature blend of minimalism and innovation, bringing a poetic yet highly functional light source to outdoor environments.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8054793317854
Mounting	Portable
Light source type	LED
Light sources included	Yes
LED type	LED Module, Edge Lighting
Number of lamps	1
Source flux (lm)	182
Lumen Output (lm)	115

Physical

Colour	Pale Green
Trim	No
Orientation	Fixed
Net weight (kg)	2.5
Package height (mm)	495
Package width (mm)	200
Package length (mm)	180
Package volume (m3)	0.02
IP internal	65

Download

Mounting instructions

PDF

Photometric Files

LDT / IES

ZIP

Technical Drawings


2D ZIP

3D ZIP

Bim ZIP



Schematic light drawing



Beam Angle: 106°

h(m)	E(lx)	D(m)
1	45	2.64
2	11	5.29
3	5	7.93
4	3	10.58
5	2	13.22

Luminous flux luminaire
115 lm

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	106
Beam angle C90-270 (°)	106
Extreme cut off	No

Electrical

Insulation class	III
Power supply	Remote excluded
Dimmable	Yes
Dimming interface	Dimmer Integrated
Emergency	No
Batteries inside	Yes
Battery type	LI-IO
Charging socket/connector	USB-C

Notes

When setting up and maintaining the device, be particularly careful not to damage the powder coating.
Damage combined with water may lead to corrosion.
Chemical products may damage the corrosion protection.

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F

