

FLOS

03.2331.40 White

Find Me 1 Casambi integrated


Designed by Jorge Herrera, 2022



LED accent lighting module to be installed in the Micro Running Magnet system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|-------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | Power LED |
| Number of heads | 1 |
| Power (W) | 4.8 |
| System power (W) | 5.5 |
| Source flux (lm) | 463 |
| System flux (lm) | 289 |
| Efficacy (lm/W) | 35 |

Physical

| | |
|--------------------------|------------|
| Colour | White |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 90 |
| Spot diameter (mm) | 33 |
| Length (mm) | 41 |
| Net weight (kg) | 0.11 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only)
light source by a
professional

Photometric

| | |
|--------------------------|-------------------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| Rf fidelity index | 91 |
| Rg gamut index | 98 |
| LED Life / Failure Ratio | L95B11 > 50.000h (Tc=85°C) |
| Beam angle C0-180 (°) | 20 |
| Beam angle C90-270 (°) | 20 |
| Extreme cut off | No |
| UGR _L | <10 |

Electrical

| | |
|---------------------|------------------|
| Insulation class | III |
| Forward voltage (V) | 12 |
| LED current (mA) | 400 |
| Power Supply | Remote excluded |
| Dimmable | Yes |
| Power Supply Type | Dimmable Casambi |
| Dimming range (%) | 1-100 |

Notes

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)