



05.5127.ES.CB Brushed Bronze

# Find Me 2 Casambi Dimmable NEW



Designed by FLOS Architectural, 2023




10.5W - 404lm - 3000K - CRI> 90 - Beam° 32

LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Accessories included (honeycomb grid and protection bar).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

Mouriurig	ITACK
Environments	Indoor dry location
Light Source Type	LED
LED type	Power LED
Number of heads	1
Power (W)	10.5
Source flux (lm)	781
System flux (lm)	404

## Physical

Colour	Brushed Bronze
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Net weight (kg)	0.3
IP internal	20

#### Download

Mounting instructions



#### Photometric Files

LDT / IES



### **Technical Drawings**

2D	₹ ZIP
3D	<b>↓</b> ZIP

















https://professional.flos.com/en/global/product/find-me-2-casambi-dimmable-05.5127.es.cb/

05.5127.ES.CB

# Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	801	0.57
2	200	1.15
3	89	1.72
4	50	2.29
5	32	2.87

Luminous flux luminaire 404 lm

# Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	765
Power Supply	Remote excluded
Dimmable	Yes
Power Supply Type	Dimmable Casambi
Dimming interface	Remote Dimmable (Dimmer Not Included)

# **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class G



Non-replaceable light source



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32
Extreme cut off	No
UGR <sub>L</sub>	<10